

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
 "Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

160.133 Lifeboat Release Mechanism (SOLAS)

BEDRIFTSVEIEN 9,KROGENES POSTBOKS 1653 ARENDAL

160.133/0001/1	APPROVED	"TOR" type, on-load release gear, approved for maximum working load of 3360	Kg (7405 lbs.) per hook.
160.133/0002/1	APPROVED	"TOR" type, on-load release gear, approved for a maximum working load of	5000 Kg (11020 lbs.) per hook.
160.133/0003/1	APPROVED	"TOR" type, on-load release gear, approved for a maximum working load of	8000 Kg (17632 lbs.) per hook.
160.133/0025/0	APPROVED	TOR ON LOAD 12T SWL release mechanism for lifeboats. Maximum safe working load 117 kN (12,00 kg) p	

ALEXANDER/RYAN MARINE & SAFETY CO 2000 WAYSIDE DRIVE P.O. BOX 9363 HOUSTON TX

160.133/0024/0	APPROVED	BG-7 release mechanism for lifeboats. Maximum safe working load 68.6 kN	(7.0 metric tons).
----------------	----------	---	--------------------

AMBAR MARINE INC. P O BOX 51271 LAFAYETTE LA 70505

160.133/0016/0	APPROVED	Model AMB-5 Rescue Boat Off-Load Release Mechanism. Maximum working load	of 5000 kg (11,000 lb) pe
----------------	----------	--	---------------------------

ERNST HATECKE GMBH JACHT- UND BOOTSWERFT POSTFACH 1107 D-21703 DROCHTERSEN GERMANY

160.133/0019/0	APPROVED	Type GFF(T)-8.1M, Free-Fall lifeboat release and holding device, approved	for a working load of 3700 kg.
160.133/0020/0	APPROVED	Simplex 1.1 single point rescue boat release mechanism (off-load version).	Maximum safe working load 10.8

FR FASSMER GMBH & CO MOTZEN-WESER D-2876 BERNE 2 GERMANY

160.133/0010/0	APPROVED	4.3 Tonne on-load mechanical disengaging apparatus, safe working load 4300	kg (9477 lbs.) per hook.
----------------	----------	--	--------------------------

NORSAFE A/S P.O. BOX 115 N-4818 FAERVIK NORWAY

160.133/0015/0	APPROVED	Norsafe 4T offload release hook, for use only with single-point suspension	rescue boats.
----------------	----------	--	---------------

SURVIVAL SYSTEMS INTERNATIONAL 34140 VALLEY CENTER ROAD P. O. BOX 1855 VALLEY CENTER CA 92082

160.133/0028/0	APPROVED	Model 504-111 Disengaging Apparatus, used only as a single hook.	
160.133/0029/0	APPROVED	Model 507-111 Disengaging Apparatus, for low temp. applications used only	as a single hook. Approved for
160.133/0030/0	APPROVED	Whittaker Model 508-111 Disengaging Apparatus, used only as a single hook.	Approved for maximum workin

UMOE SCHAT-HARDING AS N-5470 ROSENDAL

160.133/0005/0	APPROVED	Type H-80M, Group I, mechanical disengaging apparatus for lifeboats.	Maximum rated load 6,678 kg (14,
160.133/0014/0	APPROVED	Type H-80 HS, Group I, Release mechanism for lifeboats, hydraulically	operated. Maximum rated load 6,6
160.133/0026/0	APPROVED	FFH 4.0 release mechanism for free-fall lifeboats. Maximum safe working	load 32.9 kN (4.0 metric tons).

UMOE SCHAT-HARDING B.V. P.O. BOX 9032 3506 GA UTRECHT

160.133/0017/0	APPROVED	Schat type ARB 40 or type ARB 40(UJ) automatic off-load release hook, for	use with single-point suspension
160.133/0021/0	APPROVED	Schat type RRH 15 release hook, for use only with single-point suspension	rescue boats.

UMOE SCHAT-HARDING INC. 912 HIGHWAY 90 EAST NEW IBERIA LA 70560

160.133/0011/1	APPROVED	Titan Release Gear. Maximum working load 14,090 kg (31,000 lb) per set	(7045 kg (15,500 per hook).
160.133/0012/1	APPROVED	Titan Release Gear. Maximum working load of 8000 lbs per hook.	

VIKING LIFE-SAVING EQUIPMENT A/S P.O. BOX 3060 DK-6710 ESBJERG V DENMARK

160.133/0018/0	APPROVED	1.6 T rescue boat release mechanism (single fall). Maximum safe working	load 15.7 kN (1.6 metric tons).
----------------	----------	---	---------------------------------

WILLIAM MILLS (MARINE) LTD MANOR ROAD MANCHESTER LEVENSHULME ENGLAND

160.133/0006/0	APPROVED	Titan on-load release gear, approved for a maximum working load of 3000 kg	(6612 lb) per hook.
----------------	----------	--	---------------------

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

160.133/0007/0	APPROVED	Titan on-load release gear, approved for a maximum working load of 5000 kg	(11,020 lb) per hook.
160.133/0008/0	APPROVED	Titan on-load release gear, approved for a maximum working load of 6000 kg	(13,224 lb) per hook.